

# TRANSTEC 4 85W-90

**Transmission Oil** 

# **KEY DATA**

**GEAR OIL FOR MECHANICAL GEARBOXES** 

SAE 85W-90

INTERNATIONAL STANDARDS

API GL-4

### APPLICATIONS

TRANSTEC 4 85W-90 is designed for gear boxes, mild loaded axles, transfer boxes and all gears requiring API GL-4 level. TRANSTEC 4 85W-90 is specially recommended for ZF hypoid gears, with standard drain interval. Suitable for DAF, IVECO, RENAULT TRUCKS, VOLVO...etc

#### CUSTOMERS BENEFITS

- Efficient protection of gears against wear and corrosion due to stable extreme-pressure properties of the formula, but also anticorrosion and anti-rust properties.
- Enhanced compatibility with oil filters due to boosted antifoam properties.
- Efficient stability in operation due to high viscosity index.

## CHARACTERISTICS<sup>2</sup>

TEST	UNIT	TEST METHOD	RESULT
Viscosity grade	-	-	85W-90
Kinematic viscosity at 40°C	mm²/s		
Kinematic viscosity at 100°C	mm²/s		
Viscosity Index	-		
Flashpoint	°C		
Pour point	°C		
Density	Kg/m <sup>3</sup>		

<sup>2</sup> The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

#### RECOMMENDATIONS FOR USE

Before using the product, the vehicle's maintenance guide should be checked. Oil changes should be carried out in accordance with the manufacturer's recommendations. The product should not be stored at temperatures over 60°C.It should be kept away from sunlight, intense cold and extreme temperature fluctuations. If possible, the packaging should not be exposed to the elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the product's label from rubbing off.

#### HEALTH, SAFETY AND THE ENVIRONMENT

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet (SDS). This can be obtained on request from your local reseller and is available for consultation at <a href="http://sdstotalms.total.com">http://sdstotalms.total.com</a>. This product should not be used for any purposes other than the ones for which it is intended.

TOTAL LUBRIFIANTS – Immeuble Spazio 562, avenue du Parc de l'île 92029 Nanterre cedex France

TRANSTEC 4 85W-90 Last update of this datasheet: 02/2021

Some variations can be expected under normal production conditions, but these should not affect the product's expected performance irrespective of the site. The information contained in this document is subject to change without notice. Our products can be viewed on our website at <u>www.lubricants.total.com</u>.